

## Jeux de 2 tarauds - Gaz

HSS DIN 5157 (BSP) GAZ  
 Classe ISO 228  
 Nuance HSS  
 Coupe à droite  
 Goujures droites



	$\overset{\cdot}{\underset{\cdot}{\text{mm}}}$ Ø	$\overset{\cdot}{\underset{\cdot}{\text{mm}}}$ Pas	$\overset{\cdot}{\underset{\cdot}{\text{mm}}}$	$\overset{\cdot}{\underset{\cdot}{\text{mm}}}$ Queue	$\overset{\cdot}{\underset{\cdot}{\text{mm}}}$ □
998.0400	G 1/8"	28	63	7	5,5
998.0401	G 1/4"	19	70	11	9,0
998.0403	G 1/2"	14	80	16	12,0
998.0405	G 3/4"	14	90	20	16,0
998.0407	G 1"	11	100	25	20,0

## Filières extensibles HSS

DIN EN 22568 DIN 223

HSS DIN EN 22568  
 Coupe à droite  
 Goujures droites

	$\overset{\cdot}{\underset{\cdot}{\text{mm}}}$ Ø	$\overset{\cdot}{\underset{\cdot}{\text{mm}}}$ Pas	$\odot$ mm	$\overset{\cdot}{\underset{\cdot}{\text{mm}}}$ Epaisseur
332.0030	M3,0	0,50	20	5
332.0040	M4,0	0,70	20	5
332.0050	M5,0	0,80	20	7
332.0060	M6,0	1,00	20	9
332.0070	M7,0	1,00	25	9
332.0080	M8,0	1,25	25	9
332.0090	M9,0	1,25	25	11
332.0100	M10	1,50	30	11
332.0115	M11	1,50	30	10
332.0120	M12	1,75	38	10
332.0140	M14	2,00	38	10
332.0160	M16	2,00	45	18
332.0180	M18	2,50	45	14
332.0200	M20	2,50	45	14

